

## TECHNICAL DATA SHEET

PRODUCT NAME: **SPRAY CHALK** WHITE & COLORS

PRODUCT DESCRIPTION: Unique spray chalk, packaged in aerosol cans. Low odor contains water, to mark temporary-removable lines on Synthetic Field Turf Athletic Fields or special purpose markings, signs, logos, lines that wear off under normal use or can easily be removed-cleaned up with soap and water.

PRODUCT FEATURES: Packaged in aerosol cans for convenient spray applications. It is high in percent solids and low in percentage of harmful solvents. Aerosol Spray CHALK cans will empty completely and will not clog or sputter during spray application resulting in crisp sharp lines. Available in WHITE, BLUE, YELLOW, RED, BLACK, PURPLE, ORANGE, SEVERAL STANDARD & CUSTOM COLORS.

RECOMMENDED USES: To paint temporary / removable lines of various colors on Football, Soccer, Baseball, Lacrosse, Field Hockey on Synthetic / Artificial Turf Athletic Fields. Temporary or Removable marking, identifications, signs, logos, lines on asphalt, concrete, masonry, wood, walls.

SURFACE PREPARATION : Substrates must be dry and free of dirt and grease.

APPLICATION : Shake can till the ball in the can rattles and a minute after that to make sure the paint is properly mixed and is homogenous. Install con in correct spray machine. During application and drying the air and surface temperature should be between 50 – 90 degrees F. Since the propellant is flammable make sure that there are no opens flames or sources of spark close to the spray and when using in-doors make sure there is proper ventilation and proper safety precautions are taken.

## SPECIFICATIONS

Resin Type: NA

Container: 18 ounces by weight, 20 ounces by volume,  
aerosol cans. LTD QTY

Color: White, Red, Blue, Yellow, Black, Purple, custom colors

Viscosity: 120 -125 KU.

Finish: Flat

Weight Solids : 52 - 55 %.

Volatile Organic Compounds: Max 60%  
(includes aerosol propellant)

Drying Time: at 77 deg. 50 % RH, maximum 30 minutes.

Weight per Gallon: 9.5 depends on color.

Coverage: 330 lineal feet per can

Clean-up: With soap and water.

Grind: 5 Hegman minimum.

Weight Pigments: 48 – 50 %

Water Resistance: Very good

IMDG: LTD QTY

Flash point (propellant) < -60 °C (< -76 °F) ASTM D 92

Packaged : 12, 20 ounce cans per case

DOT Shipping : LTD QTY

Storage: Protect from Freezing.

Disclaimer: There are no warranties which extended beyond the information in the TDS. USSC warrants this product to conform to its own specifications. Manufacturer's liability on this warranty is limited to the return of the purchase price of this product.

The buyer assumes all risks and liability resulting from the use of this product. USSC neither assumes nor authorizes any person to assume for it any other liability in connection with the sale or use of this product. Request a MSDS if needed.

Extreme heat might make this product remove with difficulty from some types of synthetic turf. Test for removal issues by spraying inconspicuous spot in full sun. Allow spot to stand for a day before attempting to remove with a brush. Liquid removers are available to assist.