

TECHNICAL DATA SHEET

PRODUCT NAME: STRIPE- X ez Remove WHITE & COLORS.

PRODUCT DESCRIPTION: **STRIPE-X ez Remove** is a specially formulated water-based coating to be applied as a durable yet a true removable line and logo marking paint on various substrates. The salient feature of STRIPE-X ez Remove COATING is that it can be chemically dissolved and then washed away by using a safe water-based STRIPE-X REMOVER and rinse water. It is available in several standard colors and also can be blended in custom colors.

PRODUCT FEATURES: Dries quickly to a Durable, satin finish. Excellent coverage. STRIPE-X ez Remove is non-toxic to the applicator and to the environment. STRIPE-X ez Remove paint forms a good bond even on hard to stick surfaces like plastic filaments of Synthetic Turf Fields / Artificial Grass.

RECOMMENDED USES: Can be used on all interior and exterior surfaces. Asphalt, Concrete, and **Synthetic Field Turf Athletic Fields** of all types of filaments and backing materials.

SURFACE PREPARATION: For optimum performance, all surfaces must be dry, free of excessive dirt, oil or grease. The temperature during application, drying and removal must be above 50 degrees Fahrenheit or the paint will take a longer time to dry. Extremely high humidity or cold temperatures during application of the coating could lead to bad paint performance.

APPLICATION PROCEDURE:

Brush: A good quality synthetic or nylon brush.

Roller: Can be applied with all kinds of Rollers. Long nap rollers are recommended.

Spray: Can be applied with all Airless and Conventional spray equipment.

General specs for Air-less Spray Machines: Graco LineLazer Striper
Tip Sizes – Min .013, Max .027
Filter - 60 mesh
Pressure: 1800 - 2800 psi.

SPECIFICATIONS

COLOR: WHITE & various Standard and Custom colors.

FINISH: Satin

WEIGHT PER GALLON: 9.0 – 9.2

DRYING TIME: Max. 60 minutes. at 77 deg. F at 55% RH.

VISCOSITY: 85 - 90 KU.

Fineness of GRIND: 5.

HIDING POWER: Minimum 93 % contrast ratio @ 8 mil thickness of neat paint.

SOLIDS by Weight : 21 - 30 %

VOC: less than 1.04 #'s / gallon or less than 125 gms / liter.

ADHESION to polyethylene and polypropylene filament: Good.

Durability: Good

THINNING: Spray as is or Up to one gallon of **WATER** per gallon of paint.

COVERAGE: app. 900 lineal feet per gallon of paint or 300 square feet per gallon minimum.

TINTING: with universal water-base colorants to match custom colors if needed.

CLEAN-UP: Warm soap and water. Accidental over-spray can be removed by a water and soap rinse prior to drying. When using on indoor or outdoor Synthetic Turf Athletic Fields STRIPE-X ez Remove must be allowed to completely dry to prevent rub-off on uniforms.

FLASH POINT: None. Non-Flammable.

CONTAINER: 5 gallon buckets with silk screen imprint. Lids with tear away tabs and must be resealable.

FREEZE-THAW: Avoid freezing.

SHELF LIFE: 2+ years.

REMOVING PROCEDURE: Spray the STRIPE-X REMOVER over the STRIPE-X ez Remove COATING that needs to be removed. Let remover soak for 5 minutes. Next, scrub with stiff bristle brush or power scrubber or use gentle pressure washing. Rinse loose paint and remover mixture with water and the STRIPE-X coating will be completely washed away / removed. For stubborn or baked on coating that has been on turf for a while, just repeat this procedure. The wash off is non-toxic and the run off is safe to dispose in the sewer system.

Meets Federal Regulations for lead and other heavy metals and existing air pollution laws.

CAUTION: Always keep full and empty containers after use, closed and away from the reach of children. Avoid prolonged contact with skin, eyes or breathing of mist. Use with adequate ventilation. Do not take internally. In medical emergency, refer to **Material Safety Data Sheet (MSDS)** provided or request one.

Disclaimer: There are no warranties which extended beyond the information in the TDS. USSC warrants this product to conform to its own specifications. Manufacturer's liability on this warranty is limited to the return of the purchase price of this product. The buyer assumes all risks and liability resulting from the use of this product. USSC neither assumes nor authorizes any person to assume for it any other liability in connection with the sale or use of this product.

(page 2 of 2 Stripe-X ez Remove WHITE & COLORS)