

## TECHNICAL DATA SHEET

### **PRODUCT NAME: STRIPE- X REMOVER.**

**PRODUCT DESCRIPTION:** **STRIPE-X Remover** is a specially formulated water-based, safe liquid mixture to be applied on already cured STRIPE-X coatings. The chemistry is so designed to activate and dissolve the STRIPE-X coating so it can be lifted / separated from the substrate and washed away / removed. Unique to USSC, for ease of application, it also packaged in aerosol cans.

**PRODUCT FEATURES:** STRIPE-X is water-based and does not contain harmful flammable solvents. It is relatively non-toxic to the applicator and to the environment. As with any chemicals, adequate hygiene and precautions have to be taken during storage, use and disposal of this product.

**RECOMMENDED USES:** For use on all interior and exterior surfaces, namely Asphalt, Concrete, and indoor and outdoor **Synthetic Field Turf Athletic Fields** of all filament types to remove existing STRIPE-X paint.

**SURFACE PREPARATION:** Temperature during application, soaking, scrubbing and rinsing must be above 50 degrees Fahrenheit or the removal process will be slow and sluggish.

### **APPLICATION PROCEDURE:**

**Brush:** A good quality synthetic or nylon brush.

**Roller:** Can be applied with all kinds of Rollers. Long nap rollers are Recommended.

**Spray:** Can be applied with all Airless and Conventional spray equipment. Pump-up Garden sprayers or pull behind boom sprayers.

**General specs for Air-less Spray Machines:** Graco LineLazer Striper  
Tip Sizes – Min .013, Max .027  
Filter - 60 mesh  
Pressure: 1800 - 2800 psi.

## SPECIFICATION

**COLOR:** Clear Liquid.

**FINISH:** Not applicable ( NA )

**WEIGHT PER GALLON:** 8.3 – 8.5

**DRYING TIME:** 5 mins

**VISCOSITY:** Thixotropic.

**Fineness of GRIND:** NA

**HIDING POWER:** NA

**SOLIDS by Weight :**

**VOC :** Not determined.

**ADHESION to polyethylene and polypropylene filament:** NA

**Durability:** NA

**THINNING:** NA

**COVERAGE:** app. 900 lineal feet per gallon. Couple of applications maybe be needed to completely remove stubborn baked on paint that has been on the substrate for a while.

**TINTING:** NA

**CLEAN-UP:** Warm soap and water.

**FLASH POINT:** None. Non-Flammable.

**CONTAINER:** 5 gallon buckets with silk screen imprint. Lids with tear away tabs and must be resealable.

**FREEZE-THAW:** Avoid freezing.

**SHELF LIFE:** 2+ years.

**REMOVING PROCEDURE:** Spray the STRIPE-X REMOVER over the STRIPE-X COATING that needs to be removed. Let remover soak for 5 minutes. Next, scrub with stiff bristle brush or power scrubber or use gentle pressure washing. Rinse loose paint and remover mixture with water and the STRIPE-X coating will be completely washed away / removed. For stubborn or baked on coating that has been on turf for a awhile, just repeat this procedure. The wash off is non-toxic and the run off is safe to dispose in the sewer system.

Meets Federal Regulations for lead and other heavy metals and existing air pollution laws.

**CAUTION:** Always keep full and empty containers after use, closed and away from the reach of children. Avoid prolonged contact with skin, eyes or breathing of mist. Use with adequate ventilation. Do not take internally. In medical emergency, refer to **Material Safety Data Sheet ( MSDS )** provided or request one.

**Disclaimer:** There are no warranties which extended beyond the information in the TDS. USSC warrants this product to conform to its own specifications. Manufacturer's liability on this warranty is limited to the return of the purchase price of this product. The buyer assumes all risks and liability resulting from the use of this product. USSC neither assumes nor authorizes any person to assume for it any other liability in connection with the sale or use of this product.

( page 2 of 2 Stripe-X remover )